



up to  
90 lm/w



Part Number	CCT (K)	Lumen/m	LED/m	V (Typ)	Cur	W/m	IP	EEC*
A413D2460027	2700K	380	60	24V/DC	100mm	4,8W	IP20	G
A413D246000W	3000K	380	60	24V/DC	100mm	4,8W	IP20	G
A413D246000N	4000K	420	60	24V/DC	100mm	4,8W	IP20	G
A413D246000B	6000K	400	60	24V/DC	100mm	4,8W	IP20	G

\*\* The EEC specification refers in each case to the installed LED light source(s)



Datasheet download

### 🇮🇹 Strisce a LED 24V con piega angolare IP20

- 60 led/m - 4,8W/m - LED3528
- Superiore durata nel tempo, doppio rame rinforzato.
- Possibile montaggio con pieghe a 90° o curve
- Disponibile nei colori standard 3000K, 4000K e 6000K
- Fornite in nastro da 5m e cavetto

### 🇬🇧 24V Flexible adhesive LED strips for corner bending IP20

- 60 led/m - 4,8W/m - LED3528
- High life time - Pcb in reinforced copper for better heat dissipation
- Can be bent at 90° or similar curves
- Available in standard colours 3000K, 4000K and 6000K
- Supplied in 5m reels with connecting cable