



Part Number	CCT (K)	Lumen Typ.	Lux @1m	V (Typ)	I max	W	Dimensions	EEC**
A40BAR162427	2700K	1585	440	24VDC	660 mA	16W	270 x 12 x 3	F
A40BAR16240W	3000K	1660	485	24VDC	660 mA	16W	270 x 12 x 3	F
A40BAR16240N	4000K	1705	506	24VDC	660 mA	16W	270 x 12 x 3	F
A40BAR16240B	5000K	1785	550	24VDC	660 mA	16W	270 x 12 x 3	F

\*\* The EEC specification refers in each case to the installed LED light source(s)

### 🇮🇹 Strisce rigide a LED 24VDC per uso professionale

- Adatto ad applicazioni professionali con flussi luminosi oltre 5000 lumen metro
- Installazione su profili di alluminio per la dissipazione termica
- Utilizza LED 5630
- Alimentazione 24V, +3% -10%
- Piazzole per saldatura cavi e collegamento in serie fino a 9 moduli con alimentazione su un lato; 18 moduli con alimentazione da entrambi i lati (cavi a richiesta)
- Disponibile nei colori standard 2700K, 3000K, 4000K e 5000K

### 🇬🇧 24VDC rigid LED BAR for professional use

- Suitable for professional applications requiring more than 5000 lumen per metre
- Installation in Alu Led profiles for warm dissipation
- LED 5630
- 24V operation, +3% -10 %
- Soldering pads for cables and connection in series up to 9 modules powered by one side; 18 modules powered by both sides (cables on request)
- Available in 2700K, 3000K, 4000K e 5000K