

10/13
Watt/m

CRI>80


IP 20



t_a -10°÷ +40°C



up to
170 lm/w



Part Number	CCT (K)	Lumen/m	LED/m	V (Typ)	Cut	W/m	IP	EEC*
A41D241600CT	2700+6500K	2120+2230	80+80	24V/DC	50mm	13+13W	IP20	D
A41D241610CT	2700+6500K	1620+1720	80+80	24V/DC	50mm	10+10W	IP20	D

** The EEC specification refers in each case to the installed LED light source(s)



Datasheet download

 **ALIMENTATORI SUGGERITI:**
 **RECOMMENDED DRIVERS:**



Codice/Code: **A40PBX100TWB**
TW 24V Led Driver
Page:190

 **Strisce flessibili autoadesive a LED 24V TW IP20**

- Utilizza LED 2835D doppio chip ad alta efficienza
- 80+80led/m - 13+13W/m o 10+10W/m
- Bianco dinamico 2700-6500K
- Montaggio su profili in alluminio obbligatorio
- Fornite in nastro da 5m e cavetto di raccordo

 **24V Flexible adhesive TW LED strips IP20**

- Supplied with Leds 2835D Double Chip - High Efficiency
- 80+80 led/m - 13+13W/m or 10+10W/m
- Tunable White 2700-6500K
- Installation on aluminum profiles
- Supplied in 5m reel with connecting lead

