



### Technical details

Product No.	A41D241608xx	A41D241610xx	A41D241615xx
Led Q.ty (LEDs/m)	160	160	160
Led Type	2835D	2835D	2835D
Power (W/M)	8	10	15
Voltage (V)	24 ±3%	24 ±3%	24 ±3%
Current (mA/M)	333mA	417mA	625mA
CRI (Ra)	≥ 80	≥ 80	≥ 80
Lenght/Reel (M)	5	5	5
Beam	120°	120°	120°
Water-proof rating	IP20	IP20	IP20

Non-directional or directional light source:	Non-directional (NDLS)
Mains or non-mains light source:	Non-mains (NMLS)
Dimmable:	Only with specific LED drivers
Cables type:	PVC 80°C 20AWG lenght 36cm (double ended)
Pcb material:	COPPER
Tape type:	3M 9080
Energy rating:	<b>D/C/B</b> (EU 2019/2015) *
Protection against electric shock:	Class III
Version:	Integral
Safety isolating:	See electronic controlgear
Lumen maintenance factor:	96%
Survival factor:	100%
Nominal lifetime LM-80:	L70 B50 >54000 h
Photobiological Safety (Blue light hazard) according to IEC TR 62778:	Risk Exempt (RG0 group)

\*Energy class is calculated according to Spectrum test measurements

## LED STRIPS – LED 2835D – High Efficiency – IP20 – D Serie

### Lumens per meter

Color Temperature	A41D241608xx	A41D241610xx	A41D241615xx
2700K	1440 lm	1690 lm	2550 lm
3000K	1510 lm	1730 lm	2830 lm
4000K	1590 lm	1790 lm	2760 lm
5000K	/	/	3400 lm
6000K	/	/	2790 lm


● Due to tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 10%.

### Efficacy

Color Temperature	A41D241608xx	A41D241610xx	A41D241615xx
2700K	180 lmW	169 lmW	170 lmW
3000K	189 lmW	173 lmW	189 lmW
4000K	199 lmW	179 lmW	184 lmW
5000K	/	/	227 lmW
6000K	/	/	186 lmW

● Note: "xx"=CCT 27"(2700K)/"30"(3000K)/"40"(4000K) /"50"(5000K)/"60"(6000K)

### Light distribution




### Working conditions

Working Temperature (°C)	-20 ÷ 50
Storage Temperature (°C)	-30 ÷ 80
Voltage Range (Vdc)	23 ÷ 25
Reverse Voltage (Vdc)	25
Reference temperature (Tc)	80° C

## LED STRIPS – LED 2835D – High Efficiency – IP20 – D Serie

### Dimensions



Dimensions	A41D241608xx	A41D241610xx	A41D241615xx	Tolerance
L1(mm)	5004	5004	5004	± 10
L2(mm)	25 (4 LED)	25 (4 LED)	25 (4 LED)	± 1
L3(mm)	6.25	6.25	6.25	± 0.2
L4(mm)	360	360	360	± 5
W1(mm)	7	7	7	± 0.1
H1(mm)	1.4	1.4	1.4	± 0.1

### Weight/5m reel

A41D241608xx	125 gr.
A41D241610xx	125 gr.
A41D241615xx	130 gr.

### Energy labelling (EU 2019/2015) and Ecodesign (EU 2019/2020) regulations

Part Number	N° EPREL	EU 2019/2015 Energy rating	EU 2019/2020 Compliance
A41D24160827 – 2700K	845298	C	COMPLIANT
A41D24160830 – 3000K	842123	C	COMPLIANT
A41D24160840 – 4000K	845305	C	COMPLIANT
A41D24161027 – 2700K	845321	D	COMPLIANT
A41D24161030 – 3000K	842154	C	COMPLIANT
A41D24161040 – 4000K	845384	C	COMPLIANT
A41D24161527 – 2700K	845400	D	COMPLIANT
A41D24161530 – 3000K	842171	C	COMPLIANT
A41D24161540 – 4000K	842988	C	COMPLIANT
A41D24161550 – 5000K	845423	B	COMPLIANT
A41D24161560 – 6000K	845465	C	COMPLIANT

The scan of the QR Code on the energy label of the product refers directly to the description of the model in the EPREL (EU Product Database for Energy Labelling) database, where it is possible to download the energy labels and the information sheet of the product.

In alternative, it is possible to access the database using the model registration number (EPREL ID), which you can obtain from the product supplier.

Just insert in the browser the link <https://eprel.ec.europa.eu/screen/product/lightsources/> and add the EPREL ID after the last slash.

### Safety warning

- Install in accordance with national standards and local electrical codes.
- This product must be installed and maintained by a qualified electrician.
- Only install it with Class 2 DC constant voltage driver, do not use this product if it does not comply with Class 2 standard.
- The power of drive must meet the output of the rated power, and do not exceed the specified output power.
- Use a cable with rated temperature at least 80 ° C and be certified for external connection of the electrical equipment.
- Improper electrical installation may cause the cable to overheat and cause a fire. Please use a suitable cable between the driver, the lamp, and the controller. When selecting a wire, the voltage and current must meet the rated values.
- The LED module itself and all its components must not be mechanically stressed.
- Assembly must not damage or destroy conducting paths on the circuit board.
- To avoid mechanical damage, the LED modules should be mounted securely to the intended substrate. Heavy vibration should be avoided.
- Installation of LED modules (with power supplies) needs to be made with regard to all applicable electrical and safety standards. Only qualified personnel should be allowed to perform installations.
- Observe correct polarity! Incorrect polarity will lead to no light emission and may cause damage of the LED module.
- Parallel connection is highly recommended as safe electrical operation mode. Serial connection is not recommended. Unbalanced voltage drop can cause hazardous overload and damage the LED module.
- When mounting on metallic or otherwise conductive surfaces, there needs to be an electrical isolation at soldering points between module and the mounting surface.
- Pay attention to ESD steps when mounting the module.
- Please ensure that the power supply is of adequate power to operate the total load.
- Damage by corrosion will not be honored as a materials defect claim. It is the user's responsibility to provide suitable protection against corrosive agents such as moisture and condensation and other harmful elements.
- For applications involving exposure to humidity and dust the module must be protected by a fixture or housing with a suitable protection class.
- This product is not resistant to vulcanization, LED vulcanization damage will not be compensated. It is the responsibility of the user to provide appropriate protection against harmful sulphide components.