


Dimmable LED drivers – PLV 48V – Slim Waterproof IP65

Constant voltage LED driver / Alimentatore per LED a tensione costante

Made in Italy 



Part number Codice prodotto	P out W @230V	V out DC + 5%	I out DC max @230V	λ Power Factor	Efficiency @230V	ta °C	tc °C
A40PLV10048B	100	48	2,08 A	0,98	91%	-10...+45	85
A40PLV15048B	150	48	3,12 A	0,98	94%	-10...+45	85

Features

- IP65 built-in driver
- Double or reinforced insulation
- Self-resetting protection against overtemperatures, open circuit and output short circuits
- Supplied with double insulation cable on primary side

Caratteristiche

- Alimentatore da incorporare IP65
- Isolamento doppio o rinforzato
- Protezione auto ripristinante contro le sovratemperature, il circuito aperto e il corto-circuito sul secondario
- Fornito con cavo doppio isolamento sul lato primario

Directives / Direttive:

2014/35/EU (LVD); 2014/30/EU (EMC); RoHs 2011/65/EU + 2015/863/EU (RoHs); 2009/125/ ECODESIGN regulation (EU) N° 2019/2020 and 341/2021 amendment

Standards compliance: Conformità alle norme:

EN 61347-2-13:2014 + A1:2017; EN 61347-1:2015
EN 55015:2019 + A11:2020; EN 61000-3-3:2013; EN 61547:2009;
EN IEC 61000-3-2:2019 + A1:2021
EN 63000:2018
EN IEC 62442-3:2022



Dimmable LED drivers – PLV 48V – Slim Waterproof IP65

Constant voltage LED driver / Alimentatore per LED a tensione costante

Made in Italy 


Other electrical data	
Nominal input voltage AC	220 - 240 Vac
Input voltage DC	180-250 V
Mains frequency	50/60 Hz
iTHD	8,1%
Inrush current	30 A, 15 μ s
Surge capability (L-N)	> 1 kV
Nominal output voltage DC	48 V \pm 5%
Minimum output load	10 W
Output voltage ripple (100 Hz)	< 5%
Standby power (Psb)	\leq 0,5 W
Networked stanby power (Pnet)	\leq 0,5 W
No-load proof	YES
Intended for no-load operation	NO
Output PstLM (Flicker value)	\leq 1
Output SVM (Stroboscopic effects value)	\leq 0,4
Insulation primary/secondary:	Class II SELV 3750V AC
Leakage current:	< 0,5 mA
Temperatures and operating conditions	
Ambient temperature range	-10...+45 °C
Storage temperature range	-15...+50 °C
Capabilities	
Dimmable	NO
Protections	Open load, short-circuit, overload, overtemperature
Connections	
Primary side cables	2 x 0,75 mm ² white, double insulation, 25 cm.
Secondary side cables	2 x 1,5 mm ² black and red PVC, 25 cm.
Nominal life-time	50000h @Ta 40 °C

Dimmable LED drivers – PLV 48V – Slim Waterproof IP65

Constant voltage LED driver / Alimentatore per LED a tensione costante

Made in Italy 

Product dimensions



Color & materials

Casing material:	Polycarbonate V0
Color	White

Product weight

A40PLV10048B	400 gr.
A40PLV15048B	410 gr.