



up to
120 lm/w



Strisce flessibili a LED 24V autoadesive IP20

- LED 2835
- Consumo ridotto
- Disponibile nei colori standard 3000K e 4000K
- Fornite in nastro da 5m e cavetto di raccordo.

24V Flexible adhesive LED strips IP20

- LED 2835
- Reduced consumption
- Available in standard 3000K and 4000K
- Supplied in 5m roll with connecting cable

24V LED-Streifen flexibel und selbstklebend IP20

- LED 2835
- Niedriger Verbrauch
- Farbtemperaturen verfügbar: 3000K und 4000K
- In einer 5m Rolle mit Anschlusskabel geliefert

Rubans souples à LED 24V autocollants IP20

- LED 2835
- Consommation réduite
- Disponible dans les couleurs standard 3000K e 4000K
- Fournies en ruban de 5m avec petit câble de raccordement

Tira de LED flexible adhesiva 24V IP20

- LED 2835
- Consumo reducido
- Disponible en colores estándar de 3000K y 4000K
- Se suministra en tiras de 5 mt y cable de conexión.

Part number	K	Lumen/m Typ.	LED x Meter	V (typ.)	Cutting point (mm)	W/m (typ.)	EEC**
A41ES2460030	3000K	540	60	24V DC	100mm	4,8W	F
A41ES2460040	4000K	560	60	24V DC	100mm	4,8W	F
A41ES2412030	3000K	1050	120	24V DC	50mm	9,6W	F
A41ES2412040	4000K	1120	120	24V DC	50mm	9,6W	F
A41ES2418030	3000K	1550	180	24V DC	33,3mm	14,4W	F
A41ES2418040	4000K	1630	180	24V DC	33,3mm	14,4W	F
A41ES2424030	3000K	2060	240	24V DC	25mm	19,2W	F
A41ES2424040	4000K	2160	240	24V DC	25mm	19,2W	F

** The EEC specification refers in each case to the installed LED light source(s)

