

1  
Watt

IP 66

CRI&gt;80

CE

EMC


M

M

F

 $t_a -20^{\circ}\div +40^{\circ}\text{C}$ 

III

  
10 mm


Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	EEC**
A40FLOOR2700	2700K	119	Diffused	38	350 mA	2,9V	1W	D
A40FLOOR3000	3000K	123	Diffused	40	350 mA	2,9V	1W	D
A40FLOOR4000	4000K	130	Diffused	42	350 mA	2,9V	1W	C
A40FLOOR5000	5000K	150	Diffused	46	350 mA	2,9V	1W	C
A40FLOOR000C	BLUE	20	Diffused	n.d.	350 mA	3,1V	1W	
A40FLOOR000R	RED	40	Diffused	n.d.	350 mA	2,9V	1W	
A40FLOOR000V	GREEN	90	Diffused	n.d.	350 mA	3,1V	1W	
A40FLOOR000A	AMBER	50	Diffused	n.d.	350 mA	2,9V	1W	

\*\* The EEC specification refers in each case to the installed LED light source(s)

### 🇮🇹 Spot a LED di potenza - 350mA

- Resa luminosa 119÷150 lumen
- Si monta a pressione in un foro da Ø 10mm
- Fornito standard con cavo FROR da 1m. Variante con cavo FEP da 5m (variante 242)
- Disponibile nei colori standard 2700K, 3000K, 4000K e 5000K
- Calpestable (max 90 Kg.)

### 🇬🇧 High Brightness LED spot - 350mA

- Light power 119÷150 lumen
- Pressure assembly into a Ø 10mm hole
- Supplied standard with 1m FROR cable or with 5 m FEP cable (subcode 242)
- Available in standard colours 2700K, 3000K, 4000K and 5000K
- Steppable (max 90 Kg.)

