

4,8/9,6
Watt/m

IP 20

CRI>80

 $t_a - 10^{\circ} \div +40^{\circ}C$ 

50 mm 60 led/m



25 mm 120 led/m

up to
115 lm/w

Part Number	CCT (K)	Lumen/m	LED/m	V (Typ)	Cut	W/m	IP	EEC*
A41H12060A27	2700K	480	60	12V/DC	50mm	4,8W	IP65	F
A41H12060A30	3000K	500	60	12V/DC	50mm	4,8W	IP65	F
A41H12060A40	4000K	540	60	12V/DC	50mm	4,8W	IP65	F
A41H12060A60	6000K	520	60	12V/DC	50mm	4,8W	IP65	F
A41H12120A27	2700K	920	120	12V/DC	25mm	9,6W	IP65	F
A41H12120A30	3000K	950	120	12V/DC	25mm	9,6W	IP65	F
A41H12120A40	4000K	1060	120	12V/DC	25mm	9,6W	IP65	F
A41H12120A60	6000K	1040	120	12V/DC	25mm	9,6W	IP65	F

** The EEC specification refers in each case to the installed LED light source(s)



Datasheet download

Strisce flessibili a LED 12V autoadesive IP65

- LED 2835 ad alta efficienza e a bassa caduta di tensione
- Realizzata in moduli da 3 LED - Consumo ridotto, alto rendimento
- Disponibile nei colori standard 2700K, 3000K, 4000K e 6000K
- Fornite in nastro da 5m e cavetto di raccordo.

12V Flexible adhesive LED strips IP65

- LED 2835 with high lumen efficiency and low voltage drop
- 3LED segment - Reduced consumption, higher efficiency
- Available in standard 2700K, 3000K, 4000K and 6000K
- Supplied in 5m roll with connecting cable