




Datasheet download



up to
140 lm/w



Part Number	CCT (K)	Lumen/m	Ra	LED/m	V (Typ)	Cut	W/m	IP	EEC*
A41K24120A27	2700K	580	95	120	24V/DC	FREE	4,8W	IP65	E
A41K24120A30	3000K	600	94	120	24V/DC	FREE	4,8W	IP65	E
A41K24120A40	4000K	640	94	120	24V/DC	FREE	4,8W	IP65	E
A41K24160A27	2700K	1210	94	160	24V/DC	FREE	9,6W	IP65	E
A41K24160A30	3000K	1270	93	160	24V/DC	FREE	9,6W	IP65	E
A41K24160A40	4000K	1340	94	160	24V/DC	FREE	9,6W	IP65	E
A41K24200A27	2700K	2110	95	200	24V/DC	FREE	16,8W	IP65	E
A41K24200A30	3000K	2180	94	200	24V/DC	FREE	16,8W	IP65	E
A41K24200A40	4000K	2350	94	200	24V/DC	FREE	16,8W	IP65	E
A41K24240A27 4m	2700K	2720	95	240	24V/DC	FREE	22W	IP65	E
A41K24240A30 4m	3000K	2880	94	240	24V/DC	FREE	22W	IP65	E
A41K24240A40 4m	4000K	3060	94	240	24V/DC	FREE	22W	IP65	E

** The EEC specification refers in each case to the installed light source(s)

🇮🇹 Strisce flessibili a LED 24V autoadesive IP65

- LED 2835 ad alta efficienza e a bassa caduta di tensione
- 120 led/m - 4,8W/m Taglio libero - Punto di saldatura per collegamento cavo ogni 8,3mm
- 160 led/m - 9,6W/m Taglio libero - Punto di saldatura per collegamento cavo ogni 12,5mm
- 200 led/m - 16,8W/m Taglio libero - Punto di saldatura per collegamento cavo ogni 10mm
- 240 led/m - 22W/m - Taglio libero - Punto di saldatura per collegamento cavo ogni 12,5mm
- Disponibile nei colori standard 2700K, 3000K e 4000K
- Fornite in nastro da 5m e cavetto di raccordo.

🇬🇧 24V Flexible adhesive LED strips IP65

- LED 2835 with high lumen efficiency and low voltage drop
- 120 led/m - 4,8W/m Free cutting - Soldering pad for wire connection every 8,3mm
- 160 led/m - 9,6W/m Free cutting - Soldering pad for wire connection every 12,5mm
- 200 led/m - 16,8W/m Free cutting - Soldering pad for wire connection every 10mm
- 240 led/m - 22W/m Free cutting - Soldering pad for wire connection every 12,5mm
- Available in standard 2700K, 3000K and 4000K
- Supplied in 5m roll with connecting cable