

LED Modules

Back Light BAR 24V

15,5W
Watt



IP 00

CRI>80

CE

EMC

M

M

F


ta -20°÷ +40°C











Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	Dimensions	EEC**
A40KBACK155B	6000K	1400	160°	nd	650 mA	24V	15,5W	1100 x 850 x 75	G
A40KBACK155N	4000K	1400	160°	nd	650 mA	24V	15,5W	1100 x 850x 75	G

** The EEC specification refers in each case to the installed LED light source(s)

-  **Barra a LED per retroilluminazione - 24V**
- Retroilluminazione di scritte pubblicitarie, pannelli
 - Lente 160° per retroilluminazione. Uniformità di luce garantita da 30mm
 - Disponibile nei colori 4000K e 6000K
 - Kit composto da 10 barre Led già cablate con doppio cavo
 - Barra d'alluminio autodissipante composta da 22 led, con fori di fissaggio 3mm - Sezionabile ogni 50 mm

-  **LED bar for backlighting - 24V**
- Specific for advertising boxes and panels
 - Equipped with 160° lens for thin boxes backlighting. Uniform light granted by 30mm
 - Available in colors 4000K and 6000K
 - Kit made of 10 LED bars, already equipped with double cable
 - Self dissipating aluminium bar, made up of 22 led, with 3mm fixing holes - cuttable every 50mm