

144÷300
Watt

 CV

PF
 $\lambda \geq 0,96$

IP 65



EMC



 M

 M


 F

 110

SELV

$t_a -20^{\circ} \div +45^{\circ}C$

 114mm



Part Number	Output V	Output I _{max} @ 230V	Output I _{max} @ 110V	W @230V	W @110V	Dimensions A x B x c
A40MB150000B	12V	12A	8A	144W	96W	152 x 104 x 46
A40MB300C00B	24V	12,5A	6,25A	300W	150W	152 x 104 x 46



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore da incorporare - IP65 - Classe II di isolamento
- Uscita in tensione costante, $\pm 7\%$
- Protezione autoripristinante contro le sovratemperature e i corto-circuiti sul secondario.
- Contenitore plastico termoconduttivo per dissipazione del calore, alto rapporto volume potenza
- Alimentazione: 110÷240V/AC - Uscita stabilizzata
- Fornito con cavi da 25cm (a richiesta con morsetti)

 Driver for High Brightness LEDs

- To be built in - IP65 - Insulation class II
- Output in steady voltage, $\pm 7\%$
- Self-resetting protection against overtemperatures and output short circuits
- Thermo conductive housing with high heat dissipating capacity.
- Input voltage: 110÷240V/AC - Steady output.
- Standard delivered with 25cm cables (with terminals, on request)