

48-100
WattPF
 $\lambda \geq 0,96$

IP 20




EMC



SELV

 $t_a -10^{\circ} \div +40^{\circ}C$ 

On request



Part Number	Output V	Output I _{max} @ 230V	Output I _{max} @ 110V	W @230V	W @110V	Dimensions A x B x c	
A40MD048000B	12V	4A	3A	48W	36W	205 x 51 x 35	
A40MD060000B	24V	2,5A	1,8A	60W	43W	205 x 51 x 35	•
A40MD100000B	24V	4,16A	-	100W	-	205 x 51 x 35	



Datasheet download

Alimentatore per moduli a LED

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante, $\pm 5\%$
- Alto fattore di potenza
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 110 \div 240V/AC. Modello MD100: 220 \div 240V/AC
- A richiesta, alimentazione a 230VDC

Driver for LED modules

- For independent use - IP20 - Insulation class II
- Steady voltage output, $\pm 5\%$
- High power factor
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Input voltage: 110 \div 240V/AC. Type MD100: 220 \div 240V/AC
- On request, 230VDC input voltage

