



1
Watt

IP 43

CRI>80

CE

EMC

 $t_a -20^{\circ}\div +40^{\circ}\text{C}$ 

Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	Ø	EEC**
A40MET20W027	2700K	119	Wide 40°	140	350 mA	3,2V	1W	21 mm	D
A40MET20W030	3000K	123	Wide 40°	154	350 mA	3,2V	1W	21 mm	D
A40MET20W040	4000K	130	Wide 40°	162	350 mA	3,2V	1W	21 mm	C
A40MET20W050	5000K	150	Wide 40°	181	350 mA	3,2V	1W	21 mm	C
A40MET20M027	2700K	119	Medium 30°	320	350 mA	3,2V	1W	21 mm	D
A40MET20M030	3000K	123	Medium 30°	363	350 mA	3,2V	1W	21 mm	D
A40MET20M040	4000K	130	Medium 30°	429	350 mA	3,2V	1W	21 mm	C
A40MET20M050	5000K	150	Medium 30°	462	350 mA	3,2V	1W	21 mm	C

** The EEC specification refers in each case to the installed LED light source(s)

🇮🇹 Spot a LED di potenza - 350mA

- Resa luminosa 119÷150 lumen
- Si monta in un foro da Ø 21mm con la ghiera in dotazione
- Fornito con cavo da 0,25 m
- Lente sigillata con guarnizione antivapore
- Disponibile nei colori 2700K, 3000K, 4000K e 5000K e colorati.

🇬🇧 High Brightness LED spot - 350mA

- Light power 119÷150 lumen
- Pressure assembly into a Ø 21mm hole. Shade ring included.
- Supplied with 0,25 m cable
- The optic is sealed by a steamproof gasket
- Color temperatures available: 2700K, 3000K, 4000K e 5000K. On request other LED colours

