

49÷160  
Watt

 CV

PF  
λ ≥ 0,96

IP 65

CE

EMC



M

M


F

110

SELV

ta -20°÷ +45°C

 90 mm



| Part Number  | Output V | Output I <sub>max</sub> @ 230V | Output I <sub>max</sub> @ 110V | W @230V | W @110V | Dimensions A x B x c |
|--------------|----------|--------------------------------|--------------------------------|---------|---------|----------------------|
| A40MIP05400N | 12V      | 4,08A                          | 3A                             | 49W     | 36W     | 177 x 82 x 35        |
| A40MIP11000N | 12V      | 9,16A                          | 5,9A                           | 110W    | 70W     | 177 x 82 x 35        |
| A40MIP07000N | 24V      | 2,90A                          | 2,08A                          | 70W     | 50W     | 177 x 82 x 35        |
| A40MIP16000N | 24V      | 6,66A                          | 2,90A                          | 160W    | 70W     | 177 x 82 x 35        |



Datasheet download

 **Alimentatore per LED di potenza**

- Alimentatore da incorporare - IP65 - Classe II di isolamento
- Uscita in tensione costante 12÷24VDC, ±5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Rifasatore attivo, forma compatta e basso riscaldamento
- Alimentazione: 110÷240V/AC - Uscita stabilizzata

 **Driver for High Brightness LEDs**

- To be built in - IP65 - Insulation class II
- Output in steady voltage 12÷24VDC, ±5%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits.
- Active power factor correction, compact size and reduced heating
- Input voltage: 110÷240V/AC - Steady output.

