

3÷4,2
Watt


CV+CC

PF
λ ≥ 0,6

IP 20



EMC





M

M

F


110

SELV


47 mm

ta -10°÷ +40°C


AC/DC



Part Number	Iout	Vout Led Min	Vout Led Max	Uout	W	Dimensions A x B x c
A40MN300000B	350mA	2,75	10,5*	12V	4,2W	59 x 42 x 20
A40MN500000B	500mA	2,75	7	10V	4W	59 x 42 x 20
A40MN400000B	700mA	2,75	3,5	6V	3W	59 x 42 x 20

*in CC mode



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore indipendente - IP 20 - Classe II di isolamento
- Uscita in tensione e corrente costante +/-10%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 220V÷ 240V/AC - A richiesta 110V÷ 240V/AC Uscita stabilizzata

 Driver for High Brightness LEDs

- Independent driver - IP 20 - Insulation class II
- Output in steady voltage and current +/-10%
- Self-resetting protection against overtemperatures against open circuit and against output short circuits.
- Input voltage: 220V÷ 240V/AC - On request 110V÷ 250V/AC Steady output.