

6-24
Watt

IP 00

CRI>80



EMC



ta -20° ÷ +50°C



Part Number	CCT (K)	Lumen Typ.	Led No	I (Typ)	V (Typ)	W	Dimensions A x B x H	EEC**
A40MOD281630	3000K	960	16	525mA	12V	6W	280 x 20 x 6	D
A40MOD281640	4000K	960	16	525mA	12V	6W	280 x 20 x 6	D
A40MOD283230	3000K	1200	32	1050mA	12V	12W	280 x 20 x 6	F
A40MOD283240	4000K	1200	32	1050mA	12V	12W	280 x 20 x 6	F
A40MOD563230	3000K	1920	32	525mA	24V	12W	560 x 20 x 6	D
A40MOD563240	4000K	1920	32	525mA	24V	12W	560 x 20 x 6	D
A40MOD566430	3000K	3840	64	1050mA	24V	24W	560 x 20 x 6	D
A40MOD566440	4000K	3840	64	1050mA	24V	24W	560 x 20 x 6	D

**The EEC specification refers in each case to the installed LED light source(s)

🇮🇹 Moduli Lineari a LED a corrente costante

- Schede Led compatibili ZHAGA a corrente costante
- Led 2835 alta efficienza
- Disponibile nei colori 3000K e 4000K, 3 step Mac Adam
- Autodissipante
- Morsetti rapidi di collegamento
- Compatibile con ottiche standard Ledil e Khatod

🇬🇧 Linear LED modules in constant current

- ZHAGA compatible constant current led modules
- High efficiency Led 2835
- Available in colors 3000K and 4000K, 3 steps Mac Adam
- Self dissipating
- Fast connection terminals
- Compatible with standard LEDIL and KHATOD optics

