

1 Watt

IP 20

CRI>80

CE

EMC


M

M

F

ta -20÷+40°C

III



Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	Ø	Standard size	EEC**
A40MONOZ27F0	2700K	119	Flat 45°	185	350 mA	3V	1W	35 mm	MR11	D
A40MONOZ30F0	3000K	123	Flat 45°	195	350 mA	3V	1W	35 mm	MR11	D
A40MONOZ40F0	4000K	130	Flat 45°	200	350 mA	3V	1W	35 mm	MR11	C
A40MONOZ27M0	2700K	119	Medium 30°	480	350 mA	3V	1W	35 mm	MR11	D
A40MONOZ30M0	3000K	123	Medium 30°	570	350 mA	3V	1W	35 mm	MR11	D
A40MONOZ40M0	4000K	130	Medium 30°	600	350 mA	3V	1W	35 mm	MR11	C

** The EEC specification refers in each case to the installed LED light source(s)

Spot a LED di potenza - 350mA

- Resa luminosa 119÷130 lumen
- Adatti a sostituire farette per lampadina dicroica Ø 35mm
- Fornito con cavo da 1 m e connettore MiniAmp
- Lente disponibile in due versioni: fascio medio (M) e fascio largo diffuso (Flat).
- Disponibile nei colori 2700K, 3000K e 4000K e colorati a richiesta.

High Brightness LED spot - 350mA

- Light power 119÷130 lumen
- Suitable for being built in standard Ø 35mm downlights
- Supplied with 1 m cable and Mini Amp connector
- Lens degrees available: medium beam (M) and wide diffused beam (Flat).
- Color temperatures available 2700K, 3000K and 4000K. On request other LED colours.