

NEON 4x10 (T) - IP67 - Indoor

LED 2835


9,6
Watt/m

IP 67

CRI>90




t_a -10° ÷ +40°C



Part Number	CCT (K)	Lumen/m	Ra	LED/m	V (Typ)	Cut	W/m	IP
A41N410T9627	2700K	260	96	180	24VDC	FREE	9,6W	IP67
A41N410T9630	3000K	290	96	180	24VDC	FREE	9,6W	IP67
A41N410T9640	4000K	310	96	180	24VDC	FREE	9,6W	IP67
A41KITN0410T	Kit: 10x brackets with screws, 2x caps with hole, 4 x end caps, 2 x glue tubes							
A41FIXN0410T	1 single fixing bracket with screw							
BAR0410TAL10	1mt aluminum profile							



Datasheet download



Strisce flessibili a LED 24V IP67

- Illuminazione a forma di T per un'installazione perfetta e diretta (senza profilo)
- Movimento orizzontale Ø>60mm
- 180 led/m - 9,6W/m - LED 2835
- Taglio libero - Punto di saldatura per collegamento cavo ogni 33,33mm
- Movimento orizzontale max 100mm
- Disponibile nei colori standard: 2700K, 3000K e 4000K
- Fornite in nastro da 5m e cavetto di raccordo

24V Flexible LED strips IP67

- T- shape lighting for perfect and direct fit-in installation (no profile needed)
- Horizontal (side) bending Ø>60mm
- 180 led/m - 9,6W/m - LED 2835
- Free cutting - Soldering pad for wire connection every 33,33mm
- Side bending max 100mm
- Color temperatures available: 2700K, 3000K or 4000K
- Supplied in 5m reels with connecting cable