

11,52/14,4  
Watt/m

IP 67


CRI&gt;80



ta -20° ÷ +40°C




Datasheet download



Part Number	CCT (K)	Lumen/m	LED/m	V (Typ)	Cut	W/m	IP
A41N2416H027 5m	2700K	1400	160	24VDC	50mm	14,4W	IP67
A41N2416H030 5m	3000K	1430	160	24VDC	50mm	14,4W	IP67
A41N2416H040 5m	4000K	1490	160	24VDC	50mm	14,4W	IP67
A41N2414H127 10m	2700K	950	140	24VDC	50mm	11,52W	IP67
A41N2414H130 10m	3000K	970	140	24VDC	50mm	11,52W	IP67
A41N2414H140 10m	4000K	1010	140	24VDC	50mm	11,52W	IP67
A41KIT3NEONB	Kit: 1 x spare front cap +30cm connecting cable + 1 end cap						
A41KIT4NEONB	kit: 10 x plastic clips + 10 x screws						
A41BARNEONH0	1mt aluminum profile						

Ø&gt;100mm

**🇮🇹 Strisce flessibili a LED 24V IP67**

- Fornite in nastro da 5m o 10m con cavetto di raccordo
- Rolla da 5m: 160led/m - 14,4W/m  
Rolla da 10m: 140 led/m - 11,52W/m
- Movimento verticale (TOP), Ø>100mm
- Taglio e giunzione del cavo ogni 50mm
- Strisce da incorporare direttamente senza profilo.
- Rolla da 5m fornita di 10 clips di fissaggio, 10viti, 1 tappo di chiusura, 1 tappo con ripartenza e cavo da 30cm
- Rolla da 10m fornita di 20 clips di fissaggio, 20 viti, 1 tappo di chiusura, 1 tappo con ripartenza e cavo da 30cm

**🇬🇧 24V Flexible LED strips IP67**

- 5m or 10m reel with power cable
- 5m reel: 160led/m - 14,4W/m  
10m reel: 140 led/m - 11,52W/m
- Vertical (TOP) bending bending, Ø>100mm
- Cut point and solder pad for cabling every 50mm
- Direct installation (no profile needed)
- 5m roll supplied with 10 fixing clips, 10 screws, 1 end cap, 1 front cap plus 30cm wire.
- 10m roll supplied with 20 fixing clips, 20 screws, 1 end cap, 1 front cap plus 30cm wire.