



| Part Number | CCT (K) | Lumen Typ. | Beam | Lux @1m | I (Typ) | V (Typ) | W | Dimensions | EEC** |
|--------------|---------|------------|------|---------|---------|---------|------|--------------|-------|
| A40NEO362427 | 2700K | 385 | 120° | 83 | 150 mA | 24V | 3,6W | 50 x 7 x 2,7 | F |
| A40NEO36240W | 3000K | 385 | 120° | 83 | 150 mA | 24V | 3,6W | 50 x 7 x 2,7 | F |
| A40NEO36240N | 4000K | 396 | 120° | 105 | 150 mA | 24V | 3,6W | 50 x 7 x 2,7 | F |
| A40NEO36240B | 5000K | 420 | 120° | 125 | 150 mA | 24V | 3,6W | 50 x 7 x 2,7 | F |
| A40NEO211227 | 2700K | 220 | 120° | 60 | 175 mA | 12V | 2,1W | 50 x 7 x 2,7 | G |
| A40NEO21120W | 3000K | 220 | 120° | 60 | 175 mA | 12V | 2,1W | 50 x 7 x 2,7 | G |
| A40NEO21120N | 4000K | 230 | 120° | 65 | 175 mA | 12V | 2,1W | 50 x 7 x 2,7 | G |
| A40NEO21120B | 5000K | 240 | 120° | 75 | 175 mA | 12V | 2,1W | 50 x 7 x 2,7 | G |

** The EEC specification refers in each case to the installed LED light source(s)

🇮🇹 Led di potenza a basso profilo

- Adatto a realizzare illuminazione lineare, collegamento parallelo
- Fornito senza cavi, combinazioni pre-cablate a richiesta.
- Disponibile nelle temperature 2700K, 3000K, 4000K e 5000K • Sedi per viti adatte al montaggio su dissipatore esterno

🇬🇧 High Brightness low profile LED module

- Suitable for building linear Led fixtures
- Supplied without cables. Other versions with cables on request
- Available in 2700K, 3000K, 4000K and 5000K colour temperatures
- Screw holes suitable for coupling with additional heat sink.