



Part Number	Ø	CCT (K)	Lumen/m	LED/m	V (Typ)	Cut	W/m	IP	
A41NT1811030	Ø18mm	3000K	770	360	24VDC	FREE	11W	IP65	
A41NT1811040	Ø18mm	4000K	780	360	24VDC	FREE	11W	IP65	
A41NT2314030	Ø23mm	3000K	990	280	24VDC	FREE	14W	IP65	
A41NT2314040	Ø23mm	4000K	1000	280	24VDC	FREE	14W	IP65	
A41KITNT1800	Kit: 2x front caps, 2x end caps, 1x glue tube for Ø18mm strip								
A41KITNT2300	Kit: 2x front caps, 2x end caps, 1x glue tube for Ø23mm strip								



Datasheet download

### **Strisce a LED NEON 360° 24V - IP65**

- Illuminazione uniforme a 360°, flessibile e pieghevole fino a 150mm
- Materiale superficie ad olio opaco con eccellente resistenza all'usura, anti-polvere.
- Modello NT1811: Ø18mm - 360led/m - 11w/m
- Modello NT2314: Ø23mm - 280led/m - 14w/m
- Taglio libero - Punto di saldatura per collegamento cavo ogni 33,33mm per modello Ø18mm e ogni 50mm per modello Ø23mm
- Fornite con: 10 staffette e 10 viti (modello NT1811) e 5 staffette, 10 tasselli e 10 viti (modello NT2314)
- Disponibile nei colori standard: 3000K e 4000K
- Fornite in nastro da 5m e cavetti di raccordo da 100cm su entrambi i lati

### **24V NEON LED strips 360° - IP65**

- 360° uniform lighting, flexible and easily bentable up to 150mm
- Matte oil material on the surface with excellent wear resistance, no dust
- Type NT1811: Ø18mm - 360led/m - 11w/m
- Type NT2314: Ø23mm - 280led/m - 14w/m
- Free cutting - Soldering pad for wire connection every 33,33mm for type Ø18mm and every 50mm for type Ø23mm
- Supplied with: 10 clips and 10 screws (type NT1811) and 5 clips, 10 dowels and 10 screws (type NT2314)
- Color temperatures available: 3000K and 4000K
- Supplied in 5m reels with 100cm connecting cables on both sides