



Part Number	Output V	Ouput I <sub>max</sub> @ 230V	Ouput I <sub>max</sub> @ 110V	W @230V	W @110V	Dimensions A x B x c
A40PBX10048B	48V	2,08A	1,25A	100W	60W	210 x 75 x 35
A40PBX15048B	48V	3,13A	1,25A	150W	60W	210 x 75 x 35
A40PBX20048B	48V	4,17A	1,87A	200W	90W	210 x 75 x 35



Datasheet download

### 🇮🇹 Alimentatore 48V per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante 48V, ± 5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Rifasatore attivo, costruzione compatta e basso riscaldamento.
- Morsetti rapidi
- Doppio collegamento di uscita
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 110÷240V/AC - Uscita stabilizzata. A richiesta, alimentazione a 230VDC

### 🇬🇧 Driver 48V for High Brightness LEDs

- For independent use - IP20 - Insulation class II
- Steady voltage output 48V, ± 5%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Active power factor correction, compact size and reduced heating.
- Fast terminals
- Double output.
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC - Steady output. On request, 230VDC input voltage