


DALI
DimmableY
DimmableC
Dimmable
0/1..10

Part Number	Output V	Ouput@230V I max	W @230V	Ouput@110V I max	W @110V	Dimensions A x B x C	Protocol
A40PBX75D48B	48V	1,56A	75W	1,04A	50W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH
A40PBX10D48B	48V	2,08A	100W	1,25A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH
A40PBX15D48B	48V	3,12A	150W	1,25A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH



Datasheet download

Alimentatore LED 48V dimmerabile DALI/0-10V/1-10V/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Comando DALI o pulsante (sul secondario, con memoria), 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dip-switches.
- Possibilità di sincronizzare più alimentatori
- Uscita in tensione costante 48V PWM
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Morsetti rapidi
- Doppio collegamento di uscita
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 110÷240V/AC - Uscita stabilizzata. A richiesta, alimentazione a 230VDC o specifica potenziata a 110V

48V dimmable LED Driver DALI/0-10V/1-10V/Push

- For independent use - IP20 - Insulation class II
- Dimming control by DALI or PUSH (on the secondary, with memory), 0-10V, 1-10V or potentiometer, selecting the dipswitch combination on board.
- Possible synchronization of more drivers
- Output in constant voltage 48V PWM
- Self-resetting protection against overtemperatures, open circuit and against output short circuits
- Fast terminals
- Double output.
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC - Steady output. On request, 230VDC input voltage or specific boosted 110V version



