

15÷21
Watt


CC

PF
λ ≥ 0,85

IP20



EMC





M

M

F


110

SELV


45 mm

ta -10°÷ +40°C


AC/DC



Part Number	Iout	Vout Led Min	Vout Led Max@230V	Vout Led max @110V	Uout	W @230V	W @110V	Dimensions A x B x c
A40PD312000B	350mA	8,25	43	31	48V	15W	11W	138 x 40 x 28,5
A40PD309000B	700mA	5,50	30	23	36V	21W	16W	138 x 40 x 28,5



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in corrente costante 350/700mA, ±5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Morsetti rapidi
- Alto fattore di potenza
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione : 110÷240V/AC- Uscita stabilizzata

 Driver for High Brightness LEDs

- Independent driver - IP20 - Insulation class II
- Output in steady current: 350/700mA, ±5%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Fast terminals
- High power factor
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC- Steady output.

