

16÷19  
WattPF  
 $\lambda \geq 0,85$ 



IP 20



EMC



SELV

 $t_a -10^{\circ} \div +40^{\circ}C$ 

Part Number	Output V	Output I <sub>max</sub> @ 230V	Output I <sub>max</sub> @ 110V	W @230V	W @110V	Dimensions A x B x c
A40PDV12000B	12V	1,33A	1,08A	16W	13W	138 x 40 x 28,5
A40PDV24000B	24V	0,79A	0,62A	19W	15W	138 x 40 x 28,5



Datasheet download

### Alimentatore per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante, + /-5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Doppio morsetto in ingresso
- Alto fattore di potenza
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione : 110÷240V/AC- Uscita stabilizzata

### Driver for High Brightness LEDs

- Independent driver - IP20 - Insulation class II
- Output in steady voltage, + /-5%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Double input terminal
- High power factor
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC- Steady output.