

0,72
Watt



IP 66


CRI>80



EMC



t_a -20°÷+40°C



| Part Number | CCT (K) | Lumen Typ. | Beam | Lux @1m | I (Typ) | V (Typ) | W | EEC** |
|--------------|---------|------------|------|---------|---------|-----------|--------|-------|
| A40PIN123000 | 3000K | 66 | 120° | 14 | 60 mA | 12V +/-5% | 0,72 W | D |
| A40PIN124000 | 4000K | 72 | 120° | 16 | 60 mA | 12V +/-5% | 0,72 W | C |

** The EEC specification refers in each case to the installed LED light source(s)

🇮🇹 Spot a LED di potenza - 12V

- Resa luminosa 66÷72 lumen
- Si monta a pressione in un foro da Ø 10mm
- Fornito standard con cavo FROR da 1m. Variante con cavo FEP da 5m (variante 242)
- Disponibile nelle temperature di colore 3000K e 4000K
- Calpestable (max 90 Kg.)

🇬🇧 High Brightness LED spot - 12V

- Light power 66÷72 lumen
- Pressure assembly into a Ø 10mm hole
- Supplied standard with 1m FROR cable or with 5 m FEP cable (subcode 242)
- Available in 3000K and 4000K
- Steppable (max 90 Kg.)

