

15-16,8
Watt



SELV

PF
 $\lambda \geq 0,85$

IP 20



EMC





45 mm

$t_a -10^{\circ} \div +40^{\circ}C$



Dimmable



Part Number	I _{out}	V _{out} Led Min	V _{out} Led Max	U _{out}	W	Dimensions A x B x C	Protocol
A40PLD11200B	350mA	8,25	43	45V	15W	138 x 40 x 28,5	PUSH
A40PLD30600B	700mA	5,50	24	32V	16,8W	138 x 40 x 28,5	PUSH



Datasheet download

Alimentatore dimmerabile per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Comando della luce - accensione, regolazione e spegnimento - con uno o più pulsanti
- Uscita in corrente costante 350mA ÷ 700mA, +/-10%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 110V ÷ 240V/AC - Uscita stabilizzata

Dimmable Driver for High Brightness LEDs

- For independent use - IP20 - Insulation class II
- Light control - on, off and dimming - by one or more push-buttons
- Output in steady current: 350mA ÷ 700mA, +/-10%
- Self-resetting protection against overtemperatures, open circuit and output short circuits.
- Cable clamp for flat and round cables
- Input: 110V ÷ 240V/AC - Steady output

