

50÷150
WattPF
 $\lambda \geq 0,96$

IP 65




EMC



SELV



46/60 mm

 $t_a -10^{\circ}\div +45^{\circ}\text{C}$ 

Part Number	Output V	Output I _{max}	W	Dimensions A x B x C
A40PLV05000B	24V	2,08A	50W	143 x 40 x 22
A40PLV050K0B	24V	2,08A	50W	178 x 40 x 23,5
A40PLV10000B	24V	4,16A	100W	175 x 50 x 32
A40PLV15000B	24V	6,25A	150W	175 x 50 x 32



Datasheet download

Alimentatore per LED di potenza

- Alimentatore da incorporare - IP65 - Classe II di isolamento
- Uscita in tensione costante 24VDC, $\pm 5\%$
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Alto fattore di potenza
- Alimentazione: 220÷240V/AC $\pm 10\%$ - Uscita stabilizzata

Driver for High Brightness LEDs

- To be built in - IP65 - Insulation class II
- Output in steady voltage 24VDC, $\pm 5\%$
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits.
- High power factor
- Input voltage: 220÷240V/AC $\pm 10\%$ - Steady output.

