

1
Watt



IP 40

CRI>80

CE


EMC

M

M

F

$t_a -20^{\circ}\div +40^{\circ}\text{C}$



Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	Ø	EEC**
A40POD270000	2700K	119	60° Diffused	40	350 mA	2,9V	1W	16 mm	D
A40POD300000	3000K	123	60° Diffused	45	350 mA	2,9V	1W	16 mm	D
A40POD400000	4000K	130	60° Diffused	50	350 mA	2,9V	1W	16 mm	C
A40POD500000	5000K	150	60° Diffused	55	350 mA	2,9V	1W	16 mm	C

** The EEC specification refers in each case to the installed light source(s)

Spot a LED di potenza - 350mA

- Resa luminosa 119÷150 lumen
- Si monta in un foro da Ø 16mm con la ghiera/molla in dotazione
- Fornito con cavo da 0,25 m
- Disponibile nei colori 2700K, 3000K, 4000K e 5000K

High Brightness LED spot - 350mA

- Light power 119÷150 lumen
- Assembly into a Ø 16mm hole. Shade ring/spring included.
- Supplied with 0,25 m cable
- Available in standard colours 2700K, 3000K, 4000K and 5000K

