



Part Number	Output V	Output I _{max} @ 230V	Output I _{max} @ 110V**	W @230V	W @110V**	Dimensions A x B x c
A40PT030120B	12V	2,5A	1,66A	30W	20W	165 x 41 x 27,5
A40PT035240B	24V	1,45A	0,83A	35W	20W	165 x 41 x 27,5
A40PT050240B	24V	2,08A	1,25A	50W	30W	165 x 41 x 27,5

** on request



Datasheet download

Alimentatore LED 12-24V

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante, $\pm 5\%$
- Protezione autoripristinante contro le sovratemperature e i corto-circuiti sul secondario.
- Rifasatore attivo, costruzione compatta e basso riscaldamento.
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 220÷240V/AC - Uscita stabilizzata. A richiesta, alimentazione a 110VAC

12-24V LED Driver

- Driver for independent mounting - IP20 - Insulation class II
- Steady voltage output, $\pm 5\%$
- Self-resetting protection against overtemperatures and output short circuits.
- Active Power factor correction, compact size and reduced heating.
- Cable clamp for flat and round cables
- Input voltage: 220÷240V/AC - Steady output. On request, 110VAC input voltage