

15÷18
Watt

PF
 $\lambda \geq 0,95$


IP 20

EMC

$t_a -10^{\circ}\div +40^{\circ}\text{C}$

SELV

50mm




Part Number	I _{out}	V _{out} Led Min	U _{out}	W	Dimensions A x B x C	Protocol
A40PTEMC240B	500÷750mA	2,75	34V	18W	165x 41 x 28	TRIAC/IGBT/MOSFET

A40PTEMC240B

P _o	V _o	I _o	1	2	3	4
15W	30V	500mA	○	○	○	○
17W	28V	600mA	●	○	○	○
18W	26V	700mA	●	●	○	○
18W	24V	750mA	●	●	●	●

Before use, always check dipswitch settings



Datasheet download

Alimentatore dimmerabile per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Regolazione della luce con dimmer TRIAC/IGBT/MOSFET sul lato primario per carichi resistivi e induttivi con carico minimo adeguato
- Uscita in corrente costante 500-750mA o tensione costante 24VDC, +/-5%, programmabile con DIP-switches (vedi schema)
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 220-240V/AC - Uscita stabilizzata.

Dimmable driver for High Brightness LEDs

- For independent use - IP20 - Insulation class II
- Light regulation by primary side TRIAC/IGBT/MOSFET dimmers for resistive and inductive loads with min. rated load.
- Output in steady current 500-750mA or in constant voltage 24VDC, +/-5%, settable by DIP-switches (see scheme)
- Self-resetting protection against overtemperatures against open circuit and against output short circuits.
- Cable clamp for flat and round cables
- Input voltage: 220-240V/AC - Steady output.

