

LED repeater "RGBW/RGB/Dimmer/TW"

288/576
Watt

 CV

PF
λ ≥ 0,96

IP 20

 CE

EMC

 M

 M


 F

ta -20° ÷ +40°C





 45 mm



Part Number	Control	Input Min.	Input Max	Output I _{max}	Output V _{max}	W	Dimensions A x B x C
A40PWMREP40B	RGBW/RGB/Dimmer/CT	12V	24V	4x5A 3x6A	Vin -0.1V	10W-240/480W	138 x 40 x 28,5



Datasheet download



Instruction download

 Ripetitore di segnale RGBW/RGB/Dimmer /TW

- Classe II di isolamento - Bassa tensione - IP20
- Ripete il segnale RGBW/RGB/ Dimmer o TW in ingresso e comanda il carico di uscita
- Alimentazione: 12 o 24V DC
- Uscita: strisce Led a tensione costante 12V o 24V
- Ingresso isolato Master per funzione Dimmer
- Collegamento in cascata di 10 apparecchi
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti

 Signal Repeater RGBW/RGB/Dimmer/TW

- Insulation class II - Low voltage system - IP20
- It repeats the input RGB or dimming signal and controls the output load
- Operation at 12 oder 24VDC
- Output: constant voltage LED strips 12VDC or 24VDC
- Isolated Master input for dimming system
- Cable clamp for flat and round cables
- Possible cascade connection of 10 devices



