




**50..75W**  
Replacement



QLAMP 111 - AR111

Part Number	CCT (K)	Lumen Typ.	Lux @1m 25°	Lux@1m 40°	I (Typ@12V)	V (Typ)	W	Ø	Standard Size
A40QL11127M1	2700K	840	2700	-	1250mA	12V	15W	111 mm	AR111
A40QL11130M1	3000K	880	2800	-	1250mA	12V	15W	111 mm	AR111
A40QL11140M1	4000K	1000	3100	-	1250mA	12V	15W	111 mm	AR111
A40QL11150M1	5000K	1060	3900	-	1250mA	12V	15W	111 mm	AR111
A40QL11127W1	2700K	840	-	1100	1250mA	12V	15W	111 mm	AR111
A40QL11130W1	3000K	880	-	1150	1250mA	12V	15W	111 mm	AR111
A40QL11140W1	4000K	1000	-	1500	1250mA	12V	15W	111 mm	AR111
A40QL11150W1	5000K	1060	-	1930	1250mA	12V	15W	111 mm	AR111

### Spot a LED di potenza - 15W - G53 - AR111 Retrofit

- Alimentazione universale 12V AC 50Hz...50KHz, 12V DC alto fattore di potenza, trasformatori elettronici, toroidali, elettromeccanici, batterie
- Collegamento con Faston 6,35mm o con vite
- Adatto a sostituire lampadine AR111 Retrofit
- Alta resa cromatica

### High Brightness LED spot - 15W - G53 - AR111 Retrofit

- Universal input: 12V AC 50Hz...50KHz, 12V DC high power factor, electronic transformers, toroidal transformers, electromechanical transformers, batteries
- 6,35 mm Fastonconnectors or with screw
- Suitable for replacing AR111 retrofit lamps
- High CRI

