





Datasheet download



DALI RGB-AF DT8



Part Number	Protocol	Iout 2 CH	Iout 1 CH	Vout Min.	Vout Max.	Uout	W	Dimensions A x B x C
A40RCC100TWB	DALI DT8/ PUSH	2 x 250÷500mA	1 x 500÷1000mA	6V	50V	55V	90W	207 x 76 x 35



Alimentatore CC per LED Bianco Dinamico 2 canali

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Per LED Bianco Dinamico a corrente costante
- Uscita in corrente costante 2 x 250÷500mA, programmabile con DIP-switches
- Ingresso pulsante bassa tensione e ingresso pulsante alta tensione. Comando della luce - accensione, regolazione e spegnimento - con uno o più pulsanti
- Collegamento in parallelo fino a max 20 x RGBBox comandati dallo stesso pulsante senza limiti di lunghezza
- Ingresso DALI
- Morsetti rapidi
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 220÷240V/AC

TW Led Driver in CC- 2 channels

- For independent mounting - IP20 - Insulation class II
- For Tunable White applications operating in constant current.
- Output in steady current: 2 x 250÷500 mA, settable by DIP-Switches
- Low voltage push button input and high voltage push button input. Light control - on, off and dimming - by one or more push-buttons (no limits of cable length)
- Parallel connection for max 20 x RGBBox controlled by the same push-buttons .
- DALI control
- Fast terminals
- Cable clamp for flat and round cables
- Input voltage: 220÷240V/AC