


3,15
Watt

IP 20

CRI>80



EMC

 $t_a -20^{\circ} \div +40^{\circ}C$ 

TRIO MR 16

Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	Ø	Standard Size	EEC**
A40TZ1627W00	2700K	357	Wide 40°	720	350 mA	8,7V	3,15W	50 mm	MR16	D
A40TZ1627M00	2700K	357	Medium 25°	1650	350 mA	8,7V	3,15W	50 mm	MR16	D
A40TZ1627N00	2700K	357	Narrow 8°	5510	350 mA	8,7V	3,15W	50 mm	MR16	D
A40TZ1630W00	3000K	370	Wide 40°	760	350 mA	8,7V	3,15W	50 mm	MR16	D
A40TZ1630M00	3000K	370	Medium 25°	1780	350 mA	8,7V	3,15W	50 mm	MR16	D
A40TZ1630N00	3000K	370	Narrow 8°	6180	350 mA	8,7V	3,15W	50 mm	MR16	D
A40TZ1640W00	4000K	390	Wide 40°	785	350 mA	8,7V	3,15W	50 mm	MR16	C
A40TZ1640M00	4000K	390	Medium 25°	1830	350 mA	8,7V	3,15W	50 mm	MR16	C
A40TZ1640N00	4000K	390	Narrow 8°	6410	350 mA	8,7V	3,15W	50 mm	MR16	C
A40TZ1650W00	5000K	450	Wide 40°	855	350 mA	8,7V	3,15W	50 mm	MR16	C
A40TZ1650M00	5000K	450	Medium 25°	2060	350 mA	8,7V	3,15W	50 mm	MR16	C
A40TZ1650N00	5000K	450	Narrow 8°	7140	350 mA	8,7V	3,15W	50 mm	MR16	C

** The EEC specification refers in each case to the installed LED light source(s)

🇮🇹 Spot a LED di potenza - 3 x 350mA

- Si adatta a faretti per lampadina microica Ø 50 mm
- Fornito con cavo da 50 cm
- Lente disponibile in tre differenti versioni: fascio stretto, medio e largo.
- Disponibile nei colori 2700K, 3000K, 4000K e 5000K

🇬🇧 High Brightness LED spot - 3 x 350mA

- Suitable for being built in standard Ø 50 mm downlights
- Supplied with 50 cm cable
- Different lens degrees available: narrow, medium and wide beam.
- Color temperatures available: 2700K, 3000K, 4000K and 5000K

