



U111 - AR111

Part Number	CCT (K)	Lumen Typ.	Lux @1m 25°	Lux@1m 40°	Lux@1m 65°	I (Typ)	V (Typ)	W	Ø	Standard Size	EEC**
A40U11127VB0	2700K	1358	4810	2680	1620	700 mA	23V	16W	111 mm	AR111	E
A40U11130VB0	3000K	1400	5150	2780	1650	700 mA	23V	16W	111 mm	AR111	D
A40U11140VB0	4000K	1421	5220	2820	1660	700 mA	23V	16W	111 mm	AR111	D
A40U11150VB0	5000K	1750	5450	2980	1730	700 mA	23V	16W	111 mm	AR111	D

** The EEC specification refers in each case to the installed LED light source(s)

Spot a LED di potenza - 7 x 700mA

- Lente a fascio variabile da 25°÷65° in tre posizioni fisse
- Assemblaggio standard con lente da 40°
- Si adatta a faretti per lampadina AR111
- Fornito con cavo da 1m e connettore MiniAmp
- Disponibile nei colori 2700K, 3000K, 4000K e 5000K

High Brightness LED spot - 7 x 700mA

- Adjustable lens beam 25°÷65° in three preset positions
- Preset beam in factory: 40°
- Suitable for being built in standard AR111 downlights
- Supplied with 1m cable and Mini Amp connector
- Available in standard colours: 2700K, 3000K, 4000K and 5000K