

19
Watt

 CC

IP 40

CRI>90

CE

EMC

M

M

F


ta -20÷+40°C



 II

 111 mm





AR111

Part Number	CCT (K)	Lumen Typ.	Beam	I (Typ)	V (Typ)	W	Ø	Standard Size	EEC**
A40U226TWSW0	2700K+6500K	2000	Superwide 70°	500mA	39V	19W	111 mm	AR111	G
A40U226TWW00	2700K+6500K	2000	Wide 45°	500mA	39V	19W	111 mm	AR111	G

** The EEC specification refers in each case to the installed light source(s)



Datasheet download

-  **Spot a LED di potenza Bianco Dinamico - AR111**
- Alimentazione in corrente costante 500mA
 - Utilizzare alimentatori DALI DT8 o pulsante con bilanciamento dei canali
 - Disponibile con riflettore wide 45° o super wide 70°
 - Si adatta in sedi per lampadina dicroica AR111 Ø 111mm con retro aperto
 - CRI 90, R9>50
 - Bianco dinamico da 2700 a 6500K

-  **High Brightness Tunable White LED spot - AR111**
- Powered in constant current 500mA
 - To be used with DALI DT8 drivers or push-button with channel balancing.
 - Available with wide 45° or super wide 70° lense.
 - Suitable for being built in standard Ø111mm AR111 downlights with open back.
 - CRI 90, R9>50
 - Tunable white from 2700K to 6500K

